

T2540/9 & T2540/24

High Speed, Mid Range Printers



Tally

DASCOM's mid range T2440/T2540 serial matrix printers are designed for applications where fast throughput and flexible paper management are vital.

Forms are easy to load as the paper is loaded either at the front or the rear of the printer. For precise paper control and to enable feeding of continuous forms, the push tractor can also be used as a pull tractor.

Both printers feature an option for 9 or 24 pin print heads to support different print quality requirements suitable for narrow and wide format printing. All printers support graphics and barcodes systems.

- **Print speeds up to 576 cps**
- **Narrow (80 columns - 2440) and wide format versions (136 columns - 2540) available**
- **Tractor feed and Manual insertion; ideal for invoices, reports, general office documents**
- **Reliable and durable**
- **USB and Parallel standard**
- **Optional integrated Ethernet (10/100BaseT) and Serial RS232 available**
- **Quick change, long life ribbon in this class**

With auto switching USB, parallel interfaces as standard and an optional Ethernet or serial interface, these new dot matrix printers offer a cost effective solution.

With high print speeds of up to 576 characters per second (cps) and the ability to handle different types of print media, including labels, invoices, reports and multi part forms, they are well suited for back office applications, including retail, local government, healthcare, warehousing and distribution.

Available Configuration:

T2540/24 - 24 pin version
T2540/9 - 9 pin version

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE





T2540/9 & T2540/24

Print Speed	9 wire printhead: At 10, 12 cpi; HS Draft: 533, 519 cps; Draft: 400, 376 cps; NLQ: 100, 100 cps; 24 wire printhead: At 10, 12 cpi: HS Draft: 480, 576 cps; Draft: 400, 480 cps; LQ: 133, 160 cps
Throughput	395 pages per hour (ECMA 132)
Character Density	10, 12, 15 (half height), 15 (full height), 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters (draft)
Memory	256Kb
Standard Connectivity	Parallel (Bi-directional), USB 2.0
Optional Connectivity	Internal Ethernet 10/100baseT, Serial RS232
Standard Emulation	9 pin: IBM® Proprinter XL, Epson® ESC/P; 24 pin: IBM® Proprinter XL24E, Epson® ESC/P2
Fonts	9 pin: HS Draft, Draft, Courier, Quadrato, OCR-B, OCR-A; 24 pin: HS Draft, Draft, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-B, OCR-A, 10 barcodes for 9 + 24 pin machines
Consumables	Ribbon: 8 million characters
Standard Paper Handling	Push or Pull tractor, friction for cut sheet
Paper Type	Continuous forms and cut forms
Forms Thickness	Max. 0.35mm
Paper Size	3-10 Inches wide
Physical Weight	Approximately – 9 pin – 18.74lbs, 24 pin – 18.74lbs
Physical Size	(HxWxD): 8 X 19 X 10 inches
Power Voltage	120V
Power Consumption	51W printing
Workload	20,000 pages per month
Number of Copies	Up to 6-part forms
Drivers	Windows 9x/ME, 2000, 2003 Server, XP, Vista
Temperature	+10°C to +40°C
Humidity	10% to 85% relative (non-condensing)
Acoustic	Less than 52dB(A) Quiet mode
Warranty	1 year return to depot

Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOPrior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

DASCOM Americas Corporation
 421 West Main Street
 Waynesboro, Virginia
 USA 22980-3606
 Tel: 877 434 1377
www.dascom.com

Copyright © 2010 DASCOM Americas Corporation
 All rights reserved. All company and product names
 are trademarks or registered trademarks of their
 respective owner. Specifications are subject to
 change without notice.

SERIAL MATRIX PRINTERS 
 MOBILE PRINTERS 
 THERMAL PRINTERS 
 LINE MATRIX PRINTERS 
 LASER PRINTERS 