

## T2265+

**High speed, rugged design for heavy duty operation**



*Tally*

The T2265+ and T2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

- **Print speeds up to 900 cps**
- **Full range of automatic features minimising operator intervention**
- **Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms**
- **Straight through paper path for easy forms loading**
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS**
- **Straight through paper path for easy forms loading**
- **Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems**

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ and T2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

- T2265+
- LA650+ DEC compatible version
- T2265+ IGP with IGP/PJL Support

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE





# T2265+

<b>Print Speed</b>	High Speed Draft: 15cpi->900cps 12cpi->840cps 10cpi->700cps
<b>Printhead Life</b>	500 million characters
<b>Throughput</b>	(ECMA 132 @ 10cpi) Letter Performance:610 pages per hour; Spreadsheet:349 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
<b>Optional Connectivity</b>	Serial RS232, adapters, Ethernet IPDS: USB parallel adapter IBM proprinter
<b>Standard Emulation</b>	MTPL + barcode/LCP, Epson LQ (Esc P/2), IBM ProPrinter XL24e
<b>Optional Emulation</b>	<b>IGP Version:</b> IGP/PGL, Code V, MT660, Printronix, P6000,HP2564C Digital/Compaq model (LA650), PCL3 (Rugged writer), Genicom ANSI.
<b>Fonts</b>	Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 Barcodes and scaleable LCP Font.
<b>Consumables</b>	Ribbon: 20 million characters
<b>STD Paper Handling</b>	Push tractors with paper parking and AGA; Cut sheet front insertion with AGA
<b>Optional Paper Handling</b>	2nd front tractor (user installable); Dual bin automatic sheet feeder, 190 sheets per bin; Face down output bin;
<b>Paper Type</b>	Continuous forms, cut sheets
<b>Paper Weight</b>	Continuous forms: 60-120gsm; Cut sheet: 60-90gsm
<b>Paper Size</b>	Length: 3" min, 22" max; Width: 3" min, 16.5" max
<b>Physical Weight</b>	Approximately 45.6 lbs (20.7kg)
<b>Physical Size</b>	24.5" x 11" x 17" (623 x 280 x 432 W x H x D mm)
<b>Power Voltage</b>	AC 230V and 120V (selectable)
<b>Power Consumption</b>	65W printing
<b>Workload</b>	40,000 pages per month
<b>Number of Copies</b>	Original +6 (up to 7 part forms); with high impact print head option Up to 9 part forms.
<b>Temperature</b>	+10° to +35°C
<b>Humidity</b>	20% to 80%
<b>Acoustic</b>	55dB(A)
<b>Warranty</b>	90 day on-site warranty

**Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**

**DASCOM Americas Corporation**  
 421 West Main Street  
 Waynesboro, Virginia  
 USA 22980-3606  
 Tel: 877 434 1377  
[www.dascom.com](http://www.dascom.com)

Copyright © 2010 DASCOM Americas Corporation  
 All rights reserved. All company and product names  
 are trademarks or registered trademarks of their  
 respective owner. Specifications are subject to  
 change without notice.

SERIAL MATRIX PRINTERS   
 MOBILE PRINTERS   
 THERMAL PRINTERS   
 LINE MATRIX PRINTERS   
 LASER PRINTERS 